



SITRAK-G5S

6x4 Cargo Cab & Chassis

SITRAK-G5S 6x4 Cargo

Weight Parameters	Kerb Weight (kg)		7360	Transmission	Model		Allison 3200		
	Axle load（kg）	Front Axle	3820		Ratio (forward)		3.49, 1.86, 1.41, 1.00, 0.75, 0.65		
		Rear Axle	3540						
	GVM(kg)		25000		Ratio (reverse)		5.03		
	Design Axle Load(kg)	Front Axle	7000	Driving axle	Model		MCY11BES		
Rear Axle		18000	Main drive Ratio		Ratio	4.63			
Capability	Max speed (km/h)		100		Diff. lock		interwheel & interaxle diff. lock		
	Min. turning diameter (m)		21.4	Front axle	Model		VPD71DS		
	Max gradeability (%)		≥30	Tire	Rim		Front 22.5×9.0 aluminium, Rear 22.5×8.25 aluminium		
	Max parking grade (%)		≥20		Types		Front 295/80R22.5-18PR Rear 11R22.5-16PR		
	fuel tank capacity (L)		300						
Dimensions	Dimension	Long (mm)	11030	Frame	Model		A trapezoidal frame with a wide front and narrow rear		
		Width (mm)	2490		Main beam cross-section (mm)		Slot Type 280×80×8		
		Hight (mm)(Unload)	3145		Side beam cross section (mm)		-		
	Wheelbase (mm)		5600+1400		Width of frame (mm)		Front 965 Rear 850		
	wheel track (mm)	Front	2072	Suspension	Model		Non-independence suspension		
		Rear	1870		Front	Parabolic springs	3		
	Approach angle (°)		17			Rear	air suspension	8 air bag	
	Departure angle (°)		12	Steering	Model		Recirculating ball hydraulic power Steering wheel		
	Front overhang (mm)		1430		Ratio		22.2 ~ 26.2:1		
	Rear overhang (mm)		2600		Max pressure of pump (kPa)		20000		
	height of fifth wheel ground clearance (mm)（unload）		-		Steering way		Steering wheel		
	Front/Rear fitting radius(mm)		-	Braking system	Working pressure (kPa)		1250		
	Cabin	Model			G5S-M	Service Braking type		Dual circuit compressed air brake	
		Passenger capacity			2	Brake power adjust type		EBS+ESC+HSA	
		Turning radius (mm)			2410	Parking brake type		Spring stored energy air cut brake	
		Model		MC07H.33-61	Electrics	Circuit type		dual	
	Engine	Displacement (L)		7.36		Operating voltage (V)		24	
Power rating kW/(r/min)		240/2200	Generator power (kW)			3			
Max torque Nm/(r/min)		1322/1200-1700	Batteries (V/Ah)			2×12/180			
Clutch		Model		None	other specification	AEBS+LDW			
	Operation		/						

The above technical parameters are for reference only. Any changes will not be notified separately

