



RAM 2500/3500 HEAVY DUTY



AUSTRALIA'S ORIGINAL PICKUP REIMAGINED



THE NEW RAM HEAVY DUTY. Built to work, tow and haul with confidence, the RAM Heavy Duty range delivers genuine Heavy Duty capability backed by advanced technology and proven engineering. Whether on the jobsite, towing a caravan across Australia or tackling demanding workloads, RAM Heavy Duty is engineered to get the job done.

Now available in two distinct 2500 models, customers can choose between the authentic V8 character of the RAM 2500 Warlock's 6.4L HEMI® V8 or the immense towing capability and torque of the RAM 2500 Laramie's High-Output 6.7L Cummins® Turbo Diesel.

With bold new styling, advanced towing technology and more capability than ever before, Australia's original Heavy Duty full-size pickup range has been reimagined to deliver the strength, confidence and performance required for the toughest jobs and biggest adventures.

Whether you prefer the character of a HEMI V8 or the uncompromising capability of a High-Output Cummins Turbo Diesel, there's a RAM Heavy Duty built to match the way you work, tow and explore.

2500 WARLOCK®



POWERTRAIN

6.4-litre HEMI® V8
Variable Valve Timing (VVT)
Multi-Displacement System (MDS)
8 Speed Automatic

INTERIOR AMENITIES

Black Cloth 40/20/40 Split Bench Seat
Manual 4-way Driver & Front Passenger Seats
Rear Folding Seat
Steering Wheel Audio Controls
Uconnect 5 NAV with 12-Inch Display Cluster
Wireless Android Auto
Wireless Apple Carplay
6 Speaker Sound System
7-Inch Digital Drivers Cluster

Automatic High-Beam Headlamp-Control
Rain-Sensitive Windshield Wipers
Dual-Zone Automatic Temperature Control
Push Button Start
Power Sliding Rear Window

EXTERIOR FEATURES

20-inch Diamond Cut Wheels
Black Door Handles
Mopar Black Tubular Side Steps
Power Heat/Fold/Telescoping Tow Mirrors
Spray-In Bed Liner
Transfer Case Skid Plate

CAPABILITY & FUNCTIONALITY

1,275kg Payload¹ (max tub load limits apply)²
LED Bed Lighting

— APPEARANCE PACKAGE —

Black Exterior Badging
Black Grille
Black Exterior Mirrors
Black Front and Rear Bumpers
Black Off-road Fender Flares
'WARLOCK' Decal

— SIX SEATING —



— FENDER FLARES —



— WHEELS —



— SIDE STEPS —



SAFETY & SECURITY

Deployable Bed Step
ParkView® Rear Back-up Camera
Trailer Brake Controller
Bilstein shocks tuned for on- and off-road use
Active Lane Management
Adaptive Cruise Control
Blind Spot Monitoring with Rear Cross-path and Trailer Detection
Drowsy Driver Detection
Forward Collision Warning with Active Braking
Hill Descent Control
ParkSense® Park Assist System
Traffic Sign Recognition
Trailer Sway Control

— BLACK GRILLE —



— UCONNECT 12" SCREEN —



¹ Based on kerb weight as per vehicle certification. Do not exceed rear axle load limits, which are a maximum based on sealed road use only. Avoid operating the vehicle at max tub load and rear axle load limits on unsealed roads. Distribution of payload in the tub may affect and impact both tub and rear axle load limits, requiring them to be reduced.

² 1,050kg maximum combined tub & tow ball load.

— COLOURS —



DIAMOND BLACK



GRANITE CRYSTAL



CERAMIC GREY



SILVER ZYNITH



BRIGHT WHITE

2500 LARAMIE®



POWERTRAIN

6.7L I6 Cummins High Output Turbo Diesel Engine
8 Speed Automatic

INTERIOR AMENITIES

Leather-Trimmed Bucket Seats with Full Length Centre Console
8-Way Power Adjustable Driver & Front Passenger Seats (with 2-Way Power Lumbar Adjust)
Heated and Ventilated Front Seats
Leather-Wrapped Heated Steering Wheel
Sunroof
Uconnect 5 NAV with 12-Inch Display Cluster
9 Speaker Alpine Sound System
12-Inch Digital Drivers Cluster
Automatic High-Beam Headlamp-Control
Power Adjustable Pedals with Memory
Rain-Sensitive Windshield Wipers
Dual-Zone Automatic Temperature Control

Dual Wireless Charging Pads

2nd-Row In-Floor Storage Bins

2nd-Row Fold Flat Floor

Power Sliding Rear Window

EXTERIOR FEATURES

18" Black Aluminium Wheels

Body Coloured Door Handles

Black Flat Wheel - To - Wheel Side Steps

Power Heat/Fold/Telescoping Tow Mirrors with Memory Function

Spray-In Bed Liner

CAPABILITY & FUNCTIONALITY

Remote Tailgate Release

LED Bed Lighting

Deployable Bed Step

Diesel Exhaust Brake with "Smart" Function

360° Surround View Camera

— APPEARANCE PACKAGE —

Black Exterior Badging

Black Grille

Mopar® Sport Performance Hood

Black Exterior Mirrors

— LUXURIOUS SEATING —



— RAMBOX® —



— WHEELS —



— SIDE STEPS —



Trailer Brake Controller

Trailer Reverse Guidance

Lockable, Drainable, RamBox Cargo Management System (Optional)

SAFETY & SECURITY

Active Lane Management

Adaptive Cruise Control

Blind Spot Monitoring with Rear Cross-path and Trailer Detection

Drowsy Driver Detection

Forward Collision Warning with Active Braking

ParkSense® Park Assist System

Traffic Sign Recognition

Trailer Sway Control

— MOPAR® SPORT HOOD —



— DUAL WIRELESS CHARGING —



— COLOURS —



FORGED BLUE



MOLTEN RED



DIAMOND BLACK



GRANITE CRYSTAL



CERAMIC GREY



SILVER ZYNITH



BRIGHT WHITE

3500 LARAMIE®



POWERTRAIN

6.7L I6 Cummins High Output Turbo Diesel Engine
8 Speed Automatic

INTERIOR AMENITIES

Leather-Trimmed Bucket Seats with Full Length Centre Console
8-Way Power Adjustable Driver & Front Passenger Seats (with 2-Way Power Lumbar Adjust)
Heated and Ventilated Front Seats
Leather-Wrapped Heated Steering Wheel
Sunroof
Uconnect 5 NAV with 12-Inch Display Cluster
9 Speaker Alpine Sound System
12-Inch Digital Drivers Cluster
Automatic High-Beam Headlamp-Control
Power Adjustable Pedals with Memory
Rain-Sensitive Windshield Wipers
Dual-Zone Automatic Temperature Control

Dual Wireless Charging Pads

2nd-Row In-Floor Storage Bins

2nd-Row Fold Flat Floor

Power Sliding Rear Window

EXTERIOR FEATURES

18" Black Aluminium Wheels

Body Coloured Door Handles

Black Flat Wheel - To - Wheel Side Steps

Power Heat/Fold/Telescoping Tow Mirrors with Memory Function

Spray-In Bed Liner

CAPABILITY & FUNCTIONALITY

Remote Tailgate Release

LED Bed Lighting

Deployable Bed Step

Diesel Exhaust Brake with "Smart" Function

360° Surround View Camera

Trailer Brake Controller

Trailer Reverse Guidance

SAFETY & SECURITY

Active Lane Management

Adaptive Cruise Control

Blind Spot Monitoring with Rear Cross-path and Trailer Detection

Drowsy Driver Detection

Forward Collision Warning with Active Braking

ParkSense® Park Assist System

Traffic Sign Recognition

Trailer Sway Control

— APPEARANCE PACKAGE —

Black Exterior Badging

Black Grille

Mopar® Sport Performance Hood

Black Exterior Mirrors

— LUXURIOUS SEATING —



— WHEELS —



— SIDE STEPS —



— MOPAR® SPORT HOOD —



— DUAL WIRELESS CHARGING —



COLOURS



FORGED BLUE



MOLTEN RED



DIAMOND BLACK



GRANITE CRYSTAL



CERAMIC GREY



SILVER ZYNITH



BRIGHT WHITE

RAM 2500/3500 SPECIFICATIONS

	2500 WARLOCK®	2500 LARAMIE®	3500 LARAMIE®
POWERTRAIN			
Engine Name	6.4L HEMI® V8	6.7L Cummins Turbo Diesel I-6 (High Output)	
Type and Description	90-degree petrol V-8 with variable cam timing and multi-displacement system	In-line six cylinder, turbocharged, intercooled diesel	
Displacement (cc)	6,417 cu. Cm	6,690 cu. Cm	
Bore x Stroke	103.9 x 94.6	107 x 124	
Valve System	Pushrod-operated overhead valves, 16 valves, eight deactivating and eight hydraulic lifters, all with roller followers	Pushrod-operated overhead valves, 24 valves, hydraulic lifters	
Fuel Injection	Sequential, multiport, electronic, returnless	Electric high-pressure common rail	
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, 356 aluminium cylinder heads with hemispherical combustion chambers	Compacted graphite iron (CGI) block cast-iron head	
Compression Ratio	10.0:1	16.2:1	
Power (SAE Net)	306 kW @ 5,600 rpm	313kW	
Torque (SAE Net)	582Nm @ 4,000 rpm	1,458Nm @ 1,800 rpm	
Max Engine Speed	5,800 rpm limited	3,200 rpm	
TRANSMISSION / TRANSFER CASE / AXLES			
Transmission Type	ZF Torqueflite HD 8HP75	ZF TorqueFlite® HD 8AP1075	
Gear Ratios	8	8	
1st	4.71	4.71	
2nd	3.14	3.14	
3rd	2.1	2.10	
4th	1.67	1.67	
5th	1.29	1.29	
6th	1	1	
7th	0.84	0.84	
8th	0.67	0.67	
Reverse	3.3	3.3	
Drive System	4x4	4x4	
Transfer Case Shift Mechanism	BW44-46 part-time with electric shift	BW44-48 part-time with electric shift	
Transfer Case Operating Modes - Locked Neutral	2WD; 4WD High; Neutral; 4WD Low	2WD; 4WD High; Neutral; 4WD Low	
Transfer Case Skid Plate	•	N/A	
Low Range Ratio	2.64	2.64	
Front Axle (mm)	235	235	
Rear Axle (mm)	292	292	

	2500 WARLOCK®	2500 LARAMIE®	3500 LARAMIE®
ELECTRICAL / MECHANICAL			
Alternator	220 AMP	220 AMP	
Battery	730 Amp Maintenance Free Battery	Dual Maintenance Free Batteries - 730AMP RHS and 600AMP LHS (Auxiliary)	
WHEELS & TYRES			
Wheels	20x8.0 Black Diamond Cut Aluminium Wheels	18x8.0 Black Aluminium Wheels	
Tyre Size	LT285/60R20E	LT275/70R18E	
Spare Tyre Full-size	18" steel	18" steel	
Wheel Load Rating (kg)	1587	1587	
BRAKES			
Brakes Front (mm)	359.9 x 39.1 disc with twin-piston pin-slider caliper and ABS		
Brakes Rear (mm)	357.9 x 34 disc with twin-piston pin-slider caliper and ABS		
Brake Power Assistance	Dual-rate, tandem diaphragm	Hydro-boost	
SUSPENSION/STEERING			
Chassis	Ladder-type frame, steel cab, double-wall steel pickup box		
Front Suspension	Three-link with track bar, coil springs, stabiliser bar, solid axle		
Rear Suspension	Five-link with track bar, coil springs, stabiliser bar, solid axle	Two-stage longitudinal leaf solid axle	
Front & Rear Heavy Duty Shock Absorbers	Bilstein Performance-Tuned Shocks	.	.
Steering	Hydraulic Assist		
Turning Circle Kerb to Kerb (m)	14.6		
LAYOUT/DIMENSIONS			
Engine	Longitudinal, front engine, transfer case		
Length (mm)	6066	6066	
Width (mm) (including mirrors)	2627	2627	
Height (mm)	2043	2037	2039
Wheelbase (mm)	3785	3785	
Track, Front (mm)	1719	1719	
Track, Rear (mm)	1704	1704	
Ground Clearance			
Front Axle (mm)	241	237	
Rear Axle (mm)	226	222	
Approach Angle (degrees)	22.9	22.9	
Departure Angle (degrees)	25.8	25.8	
Ramp Breakover Angle (degrees)	22	22	
Fuel-Tank Capacity (L)	117	117	
Cargo Tub (ft in)	6'4"	6'4"	

RAM 2500/3500 SPECIFICATIONS

	2500 WARLOCK®	2500 LARAMIE®	3500 LARAMIE®
LAYOUT/DIMENSIONS (CONTINUED)			
SAE Volume (cu m)	1.6		
Depth (mm)	511		
Distance Between Wheelhouses (mm)	1295		
Cargo Width (mm)	1687		
RamBox® Cargo Width (mm)	N/A	1270	N/A
RamBox® Cargo Management System - Capacity (L)	N/A	243 (both sides)	N/A
Tailgate Opening Width (mm)	1535		
Interior Space			
Headroom, Front (mm)	1038		
Legroom, Front (mm)	1040		
Shoulder Room, Front (mm)	1675		
Hip Room, Front (mm)	1598		
WEIGHTS & CAPABILITIES			
Towing, Maximum Unbraked° (kg)	750		
Towing, Maximum Braked** (kg)	4,500 (When fitted with 70mm Genuine Accessory - Part No. RAM-15L-215204)		
Towing, Maximum Braked** (kg)	6,700 (When fitted with genuine auxiliary gooseneck tow hitch accessory and air brakes)	8,000 (When fitted with genuine auxiliary gooseneck tow hitch accessory and air brakes)	
Towing, Maximum Tow Ball Down Weight (kg)	450	450	
Payload° (kg) NB1	1275	785 or 715 with RamBox®	795 (option)
Payload° (kg) NB2	1315 (option)	912 or 842 with RamBox® (option)	1652
Kerb Weight° (kg)	3220	3710 or 3780 with RamBox®	3700
Gross Vehicle Mass° (kg)	4495	4495	5352 (Vehicle Category Code: NB2)
Max Gross Combination Mass° (kg)	10,001	12,750	14,433
Upgrading/Derating of GVM (options)	Where nominated prior to landing in the country, 2500 Warlock may be uprated and complied to a GVM of 4,535 kg (NB2) and a payload of 1,315 kg. Consult your Dealer or Ram Trucks Australia for further details prior to ordering	Where nominated prior to landing in the country, 2500 may be uprated and complied to a GVM of 4,622 kg (NB2) and a payload of 912 kg (Standard Tub) and 842 kg (Rambox). Consult your Dealer or Ram Trucks Australia for further details prior to ordering.	Where nominated prior to landing in the country, 3500 may be derated and complied to a GVM of 4,495 kg (NB1) and a payload of 795 kg. Consult your Dealer or Ram Trucks Australia for further details prior to ordering.
Front Axle Load° (Maximum) (kg)	2495	2608	2721
Rear Axle Load° (Maximum) (kg)	2721	2721	3175

	2500 WARLOCK®	2500 LARAMIE®	3500 LARAMIE®
TOWING			
12 Pin Wiring Harness	•	•	•
Heavy Duty Tow Bar	• (up to 4.5T max braked towing+)		
Trailer Brake Control	•	•	•
ENGINE EFFICIENCY			
Diesel Exhaust Fluid (DEF) System	N/A	•	•
Warranty	3 years/100,000 km (whichever occurs first)^		
Roadside Assist	3 years/100,000 km (whichever occurs first)^		
Service Intervals	12 months or 12,000 kms (whichever occurs first)	6 months/12,000 kms (whichever occurs first)	
SAFETY TECH			
360° Surround View Camera	N/A	•	•
ABS Brakes	•	•	•
Active Lane Management	•	•	•
Adaptive Cruise Control	•	•	•
Airbags, Driver, Front Passenger, Front Seat Side & Curtain	•	•	•
Blind Spot Monitoring with Rear Cross-path and Trailer Detection	•	•	•
Child Seat Anchorage Points	3	3	3
Drowsy Driver Detection	•	•	•
Electronic Brakeforce Distribution	•	•	•
Diesel Exhaust Brake with "Smart" Function	N/A	•	•
Forward Collision Warning with Active Braking	•	•	•
Front Seat Belt Height Adjustment	•	•	•
Hill Start Assist	•	•	•
Hill Descent Control	•	N/A	N/A
ParkSense® Park Assist System	•	•	•
ParkView™ Rear Back-Up Camera	•	•	•
Pedestrian & Cyclist Detection	•	•	•
Pedestrian Emergency Braking	•	•	•
Power and Heated Door Mirrors	•	•	•
Sliding Sun Visors	•	•	•
Stability Control	•	•	•

RAM 2500/3500 SPECIFICATIONS

	2500 WARLOCK®	2500 LARAMIE®	3500 LARAMIE®
SAFETY TECH (CONTINUED)			
Traction Control	•	•	•
Traffic Sign recognition	•	•	•
Trailer Sway Control	•	•	•
Tyre Pressure Monitoring	•	•	•
INTERIOR			
USB	4	4	
USB C Ports	2	4	
Wireless Charging Pad	N/A	Dual	
Floor Console	N/A	Full Length Upgraded Floor Console	
Instrument Cluster	7" TFT Colour Display	Premium 12" digital driver information display	
Uconnect® Touchscreen	12" Touchscreen		
Navigation	•		
Apple CarPlay® and Android Auto™	Wireless		
Speakers / Sound System	6 Speaker	9 Speaker Alpine	
Steering Wheel Switches with Phone, Voice Recognition, Instrument Panel Control, Cruise Control and Transmission Control	•	•	•
Steering Wheel Mounted Audio Controls	•	•	•
Power Windows, one-touch up / down driver and front- passenger	•	•	•
Seat Adjustment, Driver	Manual 4 Way	Power 8-way with memory	
Seat Adjustment, Passenger	Manual 4 - Way	Power 8-way	
Seating Adjustment, Lumbar	N/A	Power 2-way	
Seats, Front, Heated & Ventilated	N/A	•	•
Seats, Rear	Rear Folding Seat	Leather trimmed 60/40 stadium-folding bench and centre 20% fold-down centre console with cup holder	
Remote Keyless ENTER 'N GO™	•	•	•
Remote Start	N/A	•	•
Push Button Start	•	•	•
Climate Control	Dual zone, automatic		
Sunroof - Power	N/A	•	•
Rear Sliding Cab Window	•	•	•

	2500 WARLOCK®	2500 LARAMIE®	3500 LARAMIE®
INTERIOR (CONTINUED)			
Sun Visor with Vanity Mirror	Driver Side, non-illuminated	Illuminated	Illuminated
2nd Row In-Floor Storage Bins with Removable Liners	N/A	•	•
Rear Flat Load Floor Storage	N/A	•	•
EXTERIOR			
Sport Performance Hood	N/A	•	•
Tinted Glass Windows	•	•	•
Rear Door Privacy / Deep-tint Glass	•	•	•
Front Door Acoustic Laminated Glass	N/A	•	•
Tinted Windshield Glass	•	•	•
Tub Length (ft in)	6'4"	6'4"	6'4"
Tub Type	Standard	Standard/Rambox	Standard
Bedliner	•	•	•
Tie-downs – Tub Fixed (Eight)	•	•	•
Central Locking Tailgate	•	•	•
Remote Tailgate Release	N/A	•	•
Tailgate Fully Damped / Assisted	N/A	•	•
Fixed Wheel to Wheel Painted Sidesteps	N/A	•	•
Mopar Black Tubular Side Steps Cab Length	•	N/A	N/A
Heavy Duty Tow bar	•	•	•
50mm Tow Ball Mount Kit	Genuine Accessory - Part No. RAM-15L-215202		
70mm Tow Ball Mount Kit	Genuine Accessory - Part No. RAM-15L-215204		
Tonneau Cover, Soft / Tri-fold	Accessory		
Rear Mud Flaps	•	•	•
Rain Activated Wipers	•	•	•
Adjustable Pedals, Power	N/A	•	•
Headlamps	Bi-Function Projector Headlamps		
Automatic Headlamps (Day/Night Sensor)	•	•	•
Automatic High-Beam Headlamp Control	•	•	•
Fog Lights, Front	LED		



YOUR GUIDE TO PAYLOAD AND TOWING REQUIREMENTS

When it comes to heavy loads and towing, understanding your RAM's capabilities is crucial. At Ram Trucks Australia, we prioritise safety and compliance, ensuring that you are fully informed about the engineering limits of your vehicle and your responsibilities as a road user. Each RAM variant is designed with specific maximum allowable payloads, towing capacities, and combined weight limits, all of which interact with each other and observing these maximums is essential for maintaining the vehicle's integrity and ensuring legal compliance.

Operating your RAM within these Towing Limits is not just a recommendation; it's vital for your safety and the safety of others on the road. Exceeding these capacities (whether individually or in combination) can lead to serious risks, including personal injury, vehicle damage, and financial loss. Our comprehensive guidelines will help you be aware of the complexities of payload management, towing capacities, and weight distribution, and give recommendations on how you can carry and tow securely and responsibly. Scan the QR code to access, read, and observe our Payload and Towing Requirements Guide and be sure to utilise our Towing Calculator tool to estimate the capacity and safety of your tow.



OWNERS MANUALS AND SUPPLEMENTS

Scan the QR code to access, read, and observe Owner Manuals and Supplements resources.

*4,500kg max braked towing capacity when fitted with genuine tow bar and genuine tow ball mount kit (50mm Part No. RAM-15L-215202 / 70mm Part No. RAM-15L-215204) accessory. The use of other towing equipment, such as non-genuine tow bar, tow ball accessories and coupling devices, is not recommended and may adversely impact the max braked towing capacity, engineering integrity and safety of the vehicle. Maximum braked towing capacity is subject to regulatory requirements and vehicle weight restrictions (which may require occupants and/or luggage to be restricted). Actual towing capacity depends on factors including the laden mass of the vehicle, driving conditions, and fitment of any accessories. The vehicle cannot be operated at maximum Payload capacity and maximum Towing Capacity at the same time, as this will exceed the Gross Combination Mass limit because the Ball Weight must also be factored into the calculation. Maximum vehicle capacities and specifications are for sealed road use only. Ram Trucks Australia does not recommend vehicles be operated at their maximum vehicle limits on unsealed roads or off-road tracks. Each RAM variant has specific limits, and operating within these ensures the vehicle's integrity and minimises the risk of personal injury, vehicle damage, and financial loss. Before you tow, visit www.ramtrucks.com.au/payload-and-towing-guide/ for our comprehensive guide and towing calculator.

*Max braked towing capacity when fitted with genuine auxiliary gooseneck tow hitch (2500: 82215840AB & RAM-00A-215840 / 3500: 82215839AC & RAM-00A-215839) and genuine 3" ball kit (82216058AC) accessories. The use of other towing equipment, such as non-genuine tow bar, tow ball accessories and coupling devices, is not recommended and may adversely impact the max braked towing capacity, engineering integrity and safety of the vehicle. Maximum braked towing capacity is subject to regulatory requirements and vehicle weight restrictions (which may require occupants and/or luggage to be restricted). Actual towing capacity depends on factors including the laden mass of the vehicle, driving conditions, and fitment of any accessories. The vehicle cannot be operated at maximum Payload capacity and maximum Towing Capacity at the same time, as this will exceed the Gross Combination Mass limit because the Ball Weight must also be factored into the calculation. Maximum vehicle capacities and specifications are for sealed road use only. Ram Trucks Australia does not recommend vehicles be operated at their maximum vehicle limits on unsealed roads or off-road tracks. Each RAM variant has specific limits, and operating within these ensures the vehicle's integrity and minimises the risk of personal injury, vehicle damage, and financial loss. Before you tow, visit www.ramtrucks.com.au/payload-and-towing-guide/ for our comprehensive guide and towing calculator.

*Payload and kerb weight figures are based on vehicle certification. It is the driver's responsibility to ensure: weight of fully loaded vehicles do not exceed GVM; front and rear axle load limits are not individually exceeded; the combined weight of the fully loaded vehicle (including tow ball download when towing) and trailer does not exceed the GCM; compliance to State and Territory towing regulations. Payload is the combined value of occupants, luggage, cargo, added options, accessories and tow ball download (when towing). Kerb weight includes the vehicle with a full tank of fuel and all standard equipment, excluding occupants. Additional weights of optional features, occupants, luggage, cargo, accessories and tow ball download (when towing) must be taken into account when calculating payload.

[^]Terms, conditions and exclusions at www.ramtrucks.com.au



RAMTRUCKS.COM.AU

GET A QUOTE

BOOK A TEST DRIVE

FIND A DEALER

JOIN OUR COMMUNITY:



@RamTrucksAustralia



#RamTrucksAustralia



RamTrucksAustralia

All the information in this document is accurate at the time of publication however variations and discrepancies may occur from time to time and American Special Vehicles Pty Ltd (trading as Ram Trucks Australia) insofar as is permitted by law to do so shall not be liable in any way as a result of any reliance by any person on anything contained in this document. RAM, the Ram's Head Logo, RamBox, AllSecure, ActiveAir, Active-Level, Laramie, LaneSense, ParkSense, ParkView, Rebel, TorqueFlite and Uconnect are registered trademarks and Keyless Enter 'n' Go are trademarks of FCA US LLC, used with permission. Eats Utes for Breakfast, and Unrivalled Everyday are registered trademarks of American Special Vehicles Pty Ltd. Bluetooth is a registered trademark of Bluetooth SIG, Inc. Apple CarPlay, Apple Maps, Apple Music, iPhone and Siri are registered trademarks of Apple Inc. Apple CarPlay® connectivity requires compatible iOS device. See apple.com.au for more details. Google, Google Maps, Google Play, Android and Android Auto are trademarks of Google LLC. Android Auto™ connectivity requires compatible Android device. See android.com/intl/en_au/ for more details. Ram Trucks Australia is the only RAM authorised right-hand-drive manufacturer and distributor of Ram Trucks in Australia. Overseas models may be shown. Some features and accessories shown are not standard and are at additional cost. This publication is dated September 2026. Ram Trucks Australia reserves the right to discontinue models at any time or change specifications without notice or without incurring obligation. Please consult with your authorised Ram Truck dealer for any rolling specification changes that may occur from time to time. All texts, pictures and other works published herein are subject to the copyright of FCA US LLC or Ram Trucks Australia, if not otherwise indicated. Any duplication, distribution, storage, communication, broadcast and reproduction or transmission of the contents without written approval from FCA US LLC and Ram Trucks Australia is prohibited. Ram 2500 Specifications_AU_2026_003.